

Now offering ASTM F480 8 tpi female schedule 40 threaded PVC well bottoms

Available in **flat bottoms** and **points** 

New sizes added to our line: 3/4", 1", 1 1/4", 1 1/2"

## **NEW** Product Announcement!

Additional Sizes Added to Our Molded Threaded PVC Well Bottoms

Injected molded for consistent guaranteed thread tolerances every time

> Molded from Prime Virgin PVC

Easy tightening grip tabs make well assembly fast and easy and add strength where needed most

> Male pins come with O-rings installed

Parts sold individually bagged and group bagged for cleanliness

Easily convertible to drive points

Made 100% in the USA





## Koby Now Offers the Following Sizes:

	Part Number	PVC Insert Description
NEW	BE75F	3/4" female threaded well point (ASTM F-480 8tpi)
NEW	FE75F	3/4" female threaded well flat (ASTM F-480 8tpi)
NEW	FE18F	1" female threaded well flat (ASTM F-480 8tpi)
	BE18M	1" PVC male treaded well point (ASTM F-480 8tpi)
	BE18F	1" PVC female treaded well point (ASTM F-480 8tpi)
NEW	BE125F	1 1/4" female threaded well point (ASTM F-480 8tpi)
NEW	FE125F	1 1/4" female threaded well flat (ASTM F-480 8tpi)
NEW	BE15F	1 1/2" female threaded well point (ASTM F-480 8tpi)
NEW	FE15F	1 1/2" female threaded well flat (ASTM F-480 8tpi)
	BE22M	2" PVC male treaded well point (ASTM F-480 2tpi)
	BE24M	2" PVC male treaded well point (ASTM F-480 4tpi)
	BE22F	2" PVC female treaded well point (ASTM F-480 2tpi)
	FE22M	2" PVC male treaded well flat (ASTM F-480 2tpi)
	FE24M	2" PVC male treaded well flat (ASTM F-480 4tpi)
	FE22F	2" PVC female treaded well flat (ASTM F-480 2tpi)
	Part Number	PVC Snap-In Description
	BB2	2" Snap in PVC Bell Boy Bottom (Sched.40)